



1114

WOCADIRECT
(877) 962 2645 info@wocadirect.com

WOCA MAINTENANCE PASTE - APPLICATION INSTRUCTIONS

WOCA Maintenance Paste may be used for the maintenance of all oiled wood surfaces and is especially suitable for oiled wood floors, where a higher degree of luster is desired. Maintenance Paste is available in Natural and White.

Work Instructions:

1. Wash the floor with WOCA Wood Cleaner mixing 3 ounces into each gallon of lukewarm water. For a cleaner floor, work with two buckets, one with Wood Cleaner solution, the other one with clean rinse water. Let the floor dry completely. If the paste is to be used as a second coat hours after the initial first coat is applied, cleaning with Wood Cleaner is not necessary. The cleaner should be used on floors that have been exposed to traffic.
2. Apply Maintenance Paste onto a white polishing pad in a circular motion, using approx. a quarter of the tube.
3. Polish Maintenance Paste uniformly into the floor using a standard buffer. Continue buffing until the wood appears saturated and silky mat. Apply more paste as necessary.
4. After paste has been applied, polish the entire floor with polishing cloths to remove excess paste.
5. The Maintenance Paste will normally dry in 4-6 hours.
6. Do not expose floor to water for 48 hours after finishing.
7. After 48 hours the floor may be treated with WOCA Soap to provide additional protection against wear and tear.

Tip: For fastest drying time, leave windows slightly open to ensure a steady flow of fresh oxygen.

Spread Rate: +/- 335 s.f./tube

Warning! Rags, pads or waste soaked with WOCA oil may self-ignite if improperly discarded. Immediately after use, place all rags and waste in a sealed, water filled bucket for proper disposal.

Quick link to Woca application videos: <http://shop.wocadenmark.com/we-are-here-to-help/how-to-do/>