

# GARRISON PEAKS COLLECTION

## Specification Sheet

The look of real wood in an affordable glue-down LVT construction with a beautiful satin finish.

<b>Name:</b>	Denali
<b>Code:</b>	GVPE12601
<b>Construction:</b>	Durable, dimensionally stable vinyl core
<b>Wear Layer:</b>	20 mil / 0.5 mm*
<b>Thickness:</b>	2.0 mm
<b>Width:</b>	6.25 Inches
<b>Length:</b>	48.75 Inches
<b>Edge Detail:</b>	4 Sides Bevel
<b>Finish:</b>	Anti-microbial urethane coat with ceramic bead for added protection against scuffs and abrasions, stain and wear resistance, easy care and maintenance

**Residential Warranty:** Limited 25 Years

**Commercial Warranty:** Limited 5 Years

\*Wear layer of 12 mil / 0.3 mm also available, product code GVPE12601

### PACKAGING

Planks per Carton	24
Sq. Ft. per Carton	50.53
Lbs per Carton	41.5
Cartons per Pallet	50
Sq Ft. per Pallet	2526.5
Lbs per Pallet	2180

### ENVIRONMENT AND HEALTH

Made with 100% virgin vinyl
100% Phthalate-free
Recyclable
Certified FloorScore for low VOC
Contributes to LEED credits
Produced in ISO 14001 certified facility

## TEST RESULTS

Thickness	ASTM F 386	Nominal $\pm 0.0005$ "	Meets
Size, Tolerance	ASTM F 2055	$\pm 0.016$ " per linear foot	Pass
Squareness	ASTM F 2055	0.010" max	Pass
Residual Indentation	ASTM F 1914	Average < 8%	Pass
Flexibility	ASTM F 137	1.0", no cracks or breaks	Pass
Dimensional Stability	ASTM F 2199	0.020" max.	Exceeds per linear foot
Static Coefficient of Friction/Slip	ASTM D 2047	$\geq 0.50$	Pass
Chemical Resistance	ASTM F 925	No more than slight change in surface dulling, attack or stain	Meets or Exceeds
Resistance to Heat	ASTM F 1514	$\Delta E \leq 8$	Pass
Resistance to Light	ASTM F 1515	$\Delta E \leq 8$	Pass
Static Load Limit	ASTM F 970	No visually apparent indentation	250 psi
Indoor Air Quality	FloorScore®	-	Meets Guidelines
Certified Low Emitting Product	LEED EQ4.3	-	Meets Guidelines

