

GARRISON PEAKS COLLECTION

Specification Sheet

The look of real wood in an affordable glue-down LVT construction with a beautiful satin finish.

Name:	Rainier
Code:	GVPE12602
Construction:	Durable, dimensionally stable vinyl core
Wear Layer:	20 mil / 0.5 mm*
Thickness:	2.0 mm
Width:	6.25 Inches
Length:	48.75 Inches
Edge Detail:	4 Sides Bevel
Finish:	Anti-microbial urethane coat with ceramic bead for added protection against scuffs and abrasions, stain and wear resistance, easy care and maintenance

Residential Warranty: Limited 25 Years

Commercial Warranty: Limited 5 Years

*Wear layer of 12 mil / 0.3 mm also available,
product code GVPE12602

PACKAGING

Planks per Carton	24
Sq. Ft. per Carton	50.53
Lbs per Carton	41.5
Cartons per Pallet	50
Sq Ft. per Pallet	2526.5
Lbs per Pallet	2180

ENVIRONMENT AND HEALTH

Made with 100% virgin vinyl
100% Phthalate-free
Recyclable
Certified FloorScore for low VOC
Contributes to LEED credits
Produced in ISO 14001 certified facility

TEST RESULTS

Thickness	ASTM F 386	Nominal $\pm 0.0005"$	Meets
Size, Tolerance	ASTM F 2055	$\pm 0.016"$ per linear foot	Pass
Squareness	ASTM F 2055	0.010" max	Pass
Residual Indentation	ASTM F 1914	Average < 8%	Pass
Flexibility	ASTM F 137	1.0", no cracks or breaks	Pass
Dimensional Stability	ASTM F 2199	0.020" max.	Exceeds per linear foot
Static Coefficient of Friction/Slip	ASTM D 2047	≥ 0.50	Pass
Chemical Resistance	ASTM F 925	No more than slight change in surface dulling, attack or stain	Meets or Exceeds
Resistance to Heat	ASTM F 1514	$\Delta E \leq 8$	Pass
Resistance to Light	ASTM F 1515	$\Delta E \leq 8$	Pass
Static Load Limit	ASTM F 970	No visually apparent indentation	250 psi
Indoor Air Quality	FloorScore®	-	Meets Guidelines
Certified Low Emitting Product	LEED EQ4.3	-	Meets Guidelines

